

TITANDiamond Core Drill

MULTI POWER



Titan - Diamond Core Drill

DEPTH CAPACITIES: Based on max pullback & a 25% safety factor N 5390 ft / 1643 m H 3675 ft / 1148 m P 2415 ft / 736 m

WINCH	
Wireline winch	Hydraulic motor direct drive
Capacity:	5000 ft of 3/16" cable
Level wind:	Standard

PRIME MOVER	
Standard unit	Cummins QSB6.7, 6.7 L, 6 cylinder, turbo charged diesel engine
Power:	260 HP @ 2200 RPM

HOIST	
Hoisting winch:	Pullmaster M25
Hoisting force:	25,000 lbs.
Capacity:	75 ft of 18mm cable

ROTATION UNIT	
Standard unit	XP drill head w/ Christensen chuck
Maximum opening:	4-5/8" (P size)
RPM:	1400 RPM
Torque:	6385 ft lbs
Chuck:	40,000 lbs capacity
Hydraulic motor:	Rexroth 160cc variable speed/torque piston motor
Gear ratios:	6.27:1, 3.12:1, 1.75:1, & 1:1

HYDRAULIC SYSTEM	
Controls:	Fully hydraulic, no electronics
Rod handling:	Sychronized chuck & footclamp w/ additional chuck control
System pressure:	4000 PSI
Filtration:	10 micron
Components:	Sauer Danfoss, Valvoil, Rexroth & Parker
Heat exchanger:	Water:oil
Optional:	Air:oil heat exchanger

FOOTCLAMP	
Standard unit	Christensen hydraulic open/spring closed
Maximum opening:	4-5/8" (P size)
Capacity:	40,000 lbs.

INCLUDED COMPONENTS	
Mud mixer c/w whip lines	
4000 ft of W/L cable	
1 set of rod and casing jaws/bushings	
WEIGHT 11,640 LBS	

MAST AND FEED	
Feed stroke:	132"
Pullback:	37,700 lbs.
Pulldown:	16,490 lbs
Drill angle:	45 to 90 degree
Tower:	10 ft or 20 ft rod pull capacity

OPTIONS
Tracked carrier
Skid w/ stabilizer cylinders
Diesel driven supply pump
Enclosed drill shack
Mud tank
French/Spanish labels & manual

WATER PUMP	
Standard unit	W1122B-CD (435) piston pump
Capacity:	37 GPM @ 1000 PSI



MULTI POWER PRODUCTS LTD

975 CROWLEY AVENUE KELOWNA BC CANADA V1Y 9R6 P 250.860.6969 F 250.860.3340

MULTIPOWERPRODUCTS.COM

