



Shell Gadus S4 OGXK

- Superior Wear Resistance
- Long Life
- Aluminum Complex

Premium Open Gear and Wire Rope Grease

Shell Gadus S4 OGXK is primarily designed for use in heavily loaded applications, and operations under arctic conditions, in mining equipment, shovels, draglines and excavators in open cut operations. Shell Gadus S4 OGXK is based on Aluminium Complex soap thickener and high viscosity semi-synthetic base oil containing enhanced extreme pressure and antiwear chemistry. Diluent is used to ensure low-temperature pumpability.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

- **Excellent load carrying capacity under severe operation conditions**
Grease contains selected components to ensure excellent resistance to shock and permanently heavy loads.
- **Very high mechanical and thermal stability**
Grease thickener structure is designed to resist mechanical stress and high temperature.
- **Withstanding severe operation conditions**
Like dust and dirt contamination, water, and changes in temperature. Gadus S4 OGXK is optimized for use in ambient temperatures between - 50°C to +10°C.
- **Maintain adhesive characteristic over time**
Thanks to advanced polymer technology ensuring durable protection. Forms a dark coating on metal surfaces that is adhesive and highly water resistant.
- **Low Friction**
Selected components ensure low friction characteristics, lower energy consumption and wear reduction.
- **Environmental compliance**
Shell Gadus S4 OGXK is formulated without chlorinated solvent or lead.

Main Applications



- Open gears on draglines, shovels, excavators, stackers and reclaimers
- Stickshifts
- Circle Rail and rollers
- Heavily loaded, slow moving antifriction bearings
- Bushings
- Open gears in Industrial sector such as cement, waste treatment or steel

Specifications, Approvals & Recommendations

Shell Gadus S4 OGXK is designed to meet the following specifications:

- Bucyrus International SD 4713
- P&H 464 Ver 10, 08-16
- CAT Service Bulletin SEBU6250-26 (July 2017)

For a full listing of equipment approvals and recommendations, please consult your local Shell Technical Helpdesk.

Typical Physical Characteristics

Properties			Method	Shell Gadus S4 OGXK
NLGI Consistency				00/000
Colour				Black
Soap Type				Al Complex
Base Oil (type)				Semi-synthetic
Solid Lubricant				Yes
Product Kinematic Viscosity	@40°C	cSt minimum	ASTM D2983	50 000
Cone Penetration	@25°C	0.1mm	ASTM D217	420 - 455

Properties		Method	Shell Gadus S4 OGXK
Four Ball Weld Load	kg	ASTM D2596	800
Four Ball Wear Scar	mm maximum	ASTM D2266	0.7
Four Ball Load Wear Index (LWI)	kg minimum	ASTM D2596	120
Flash Point of base fluid	°C minimum	ASTM D92	150
Rust Test		ASTM D1743	Pass
Copper Strip	24h @ 100°C	ASTM D4048	1b
Pumpability, Lincoln Ventmeter	@-50°C	seconds maximum	30
		Time to vent from 1800 psi to less than or equal to 600 psi	

These characteristics are typical of current production. Whilst future production will conform to Shell's specification, variations in these characteristics may occur.

Health, Safety & Environment

• Health and Safety

Shell Gadus S4 OGXK is unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Safety Data Sheet, which can be obtained from <http://www.epc.shell.com>

• Protect the Environment

Take used oil to an authorised collection point. Do not discharge into drains, soil or water.

Additional Information

• Operation Temperatures

General maximum operating temperature +140°C if not restricted by other equipment/application requirements.

• Advice

Advice on applications not covered here may be obtained from your Shell representative.